

Last modification

2021-10-11

## BALLY PE16-AGOM

9329501061640



The Bally pendant is the essence of pure and simple lighting design. The sphere is finely blasted opal glass resembling the surface of fresh snow. The rounded shape is continued with the minimal metal gallery. A short metal stem finishes the story of mid-century modernism. Available in 4 sizes and 3 metal finishes.

### Overview

<b>Family name</b>	Bally
<b>Item Type</b>	Pendants (PE)
<b>Mounting</b>	Surface
<b>This item includes</b>	Suspension
<b>Shade Shape</b>	Round
<b>Suspension Type</b>	Cable
<b>Usage</b>	Interior

### Color / Material

<b>Fixture Color 1</b>	Antique Gold,Opal Matt
<b>Fixture Material</b>	Metal,Glass
<b>Shade Material</b>	Glass
<b>Glass Colour</b>	Opal Matt
<b>Glass Finish</b>	Matte
<b>Cable Colour</b>	Black
<b>Cable Material</b>	Textile

### Size

<b>Fixture Diameter (cm)</b>	40.0
<b>Canopy Diameter (cm)</b>	10.0
<b>Canopy Projection (cm)</b>	4.7
<b>Suspension Length (cm)</b>	200.0

### Specification

<b>Voltage Input</b>	240V
<b>Wattage (max)</b>	25
<b>Wattage</b>	60W

All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.  
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

<b>Globe Type</b>	E27
<b>Globe / Light Source qty</b>	1
<b>Globe / Light Source included</b>	No
<b>Beam Angle</b>	360
<b>IP rating</b>	IP20
<b>Lead and Plug</b>	No
<b>Approvals</b>	AS/NZS 60598.1.2003
<b>Assembly Required</b>	Yes
<b>Box Contents</b>	Basic mounting screws,Instruction
<b>Installation Required</b>	Yes (by Licensed Electrician only)
<b>Care Instructions</b>	Do not use strong liquid cleaners,Wipe clean with a dry cloth
<b>Warranty</b>	3 Years
<b>Globe type recommended</b>	E27 - G A609E27OP860D,E27 - G A609E27OP840D,E27 - G A609E27OP830D

## Barcode

**GTIN** 9329501061640

## Image -dimensions





