



## Coot COT-1EX-60 Specifications

<b>Light Source</b>	LED   SMD3030	<b>Supply (Voltage)</b>	220-240V AC~50/60Hz
<b>Colours</b>	Black, White	<b>Temperature Rating</b>	-20°C +25°C
<b>Wattage</b>	12W	<b>Construction</b>	Seeded Glass & Aluminium
<b>Dimmable</b>	No	<b>IP Rating</b>	IP65
<b>Kelvins</b>	3000K - 4000K - 6000K	<b>Electrical Protection</b>	Class I
<b>Lumens</b>	950lm - 1050lm - 1000lm	<b>Compliance</b>	AS/NZS 60598.1, AS/NZS 60598.2.1, AS/NZS 61347.1, AS/NZS 61347.2.13, AS/NZS CISPR 15
<b>CRI</b>	CRI≥80	<b>Recommended Use   Warranty</b>	Domestic / Commercial   3 Year Replacement
<b>LED Hour Rating</b>	50000h   L80	<b>NZ/AU Driver   Driver Type</b>	KJUP121C 12Watt DC30-40V 320mA   Constant C, Isolated
<b>Beam Angle</b>	90°	<b>Net Weight   Gross Weight</b>	3.06KG   3.3KG

All fixtures must be installed by a licensed electrician. Please also consult a licensed electrician for any electrical and wiring enquiries. For technical support please contact: [customerservice@calibo.com.au](mailto:customerservice@calibo.com.au)

Also available in other configurations



[VIEW RANGE PAGE](#)

