



Exterior Lighting

GIROTRI

Exterior LED Surface Mounted Up/Down Wall Lights IP65

- Input voltage: 100-240V 50/60Hz
- Inbuilt Constant Current Driver included
- Housing & heatsink: aluminium
- Diffuser: PC
- Back plate: aluminium
- LED chips: 8pcs 3030
- Tri-CCT(3000/ 4000/ 6500K) in one fitting
- CCT switch inside the fitting
- CRI: >80
- Power factor: >0.8
- **2 stickers included which allow narrowing of beam angle at both or either end**
- **Beam angle: without sticker is 117° and with the sticker is 68.9°**
- Ambient temperature: -20 to 50°C
- Not suitable for dimming
- Suitable for 2 way switching
- Suitable for use with PIR or Microwave sensors



Back plate



Part No.	Description	Lumens			Watt	Dimensions	Box Weight	Box Dimensions	Carton Qty
		3000K	4000K	6500K					
GIROTRI1	WALL S/M Up/Dn 11W LED TRI TWIST Dark Grey Alt Beam	907lm	1103lm	957lm	11W	260x80x40mm	0.8kg	27x9x5cm	1/12

*Must be installed by a licenced electrician (Installation instructions sheet provided in each product box).

*To avoid disappointment and warranty problems, please ensure the IP rating of the chosen product is relevant for the intended use.