

Sanctuary

XL DC

Drawing broad strokes from solid timber blades, the Fanco Sanctuary creates an instant refuge from the heat.

Matte Black
Natural Blades



KF6020/219A - 86"
KF6030/219A - 92"
Without Light

KF6021/219A - 86"
KF6031/219A - 92"
With LED Light

Matte Black
Teak Blades



KF6020/218A - 86"
KF6030/218A - 92"
Without Light

KF6021/218A - 86"
KF6031/218A - 92"
With LED Light

Matte White
Whitewash Blades



KF6020/101A - 86"
KF6030/101A - 92"
Without Light

KF6021/101A - 86"
KF6031/101A - 92"
With LED Light

Matte White
Natural Blades



KF6020/119A - 86"
KF6030/119A - 92"
Without Light

KF6021/119A - 86"
KF6031/119A - 92"
With LED Light

Matte White
Teak Blades



KF6020/118A - 86"
KF6030/118A - 92"
Without Light

KF6021/118A - 86"
KF6031/118A - 92"
With LED Light

Matte Black
Black Blades



KF6020/202A - 86"
KF6030/202A - 92"
Without Light

KF6021/202A - 86"
KF6031/202A - 92"
With LED Light



8
Year
8 Year
Motor Warranty
2 year in home
+ 6 year motor
replacement

Technical Data

| | |
|-------------------|---------------------------|
| Install Location: | Indoor/Outdoor* & Coastal |
| Motor Type: | DC |
| Blade Material: | Solid Timber |
| Operation: | Remote Control |

| | |
|----------------------|------------------|
| Reversible: | Yes (via remote) |
| Timer: | 1H / 4H / 8H |
| Ceiling Mount Angle: | 0-15° |
| Blade Pitch: | 10° (Approx) |

Remote frequency 433 MHz

About the CCT LED Light



| | | |
|----------------------|----------------------|----------------------|
| 3000k 1435 Lumens | 4000k 1474 Lumens | 6000k 1461 Lumens |
|----------------------|----------------------|----------------------|

| | |
|-------------|---------------|
| Light Type: | LED (24w) |
| Dimmable: | Yes (8 Steps) |

SP13-FM004 - User Replaceable LED Light Panel. Plug in LED panel can be replaced without an electrician.



LED Light has CCT & Dimming level memory, turn your fan off / on and the same light settings will be retained

Anti-corrosive paint applied on all metal components & waterproof sealer on solid timber blades

Performance 86" Models

| Speed | Motor Wattage | RPM | Airflow (m3/hr) |
|-------|---------------|-----|-----------------|
| 1 | 12w | 78 | 3,460 |
| 2 | 15.6w | 87 | 6,569 |
| 3 | 22.2w | 98 | 9,089 |
| 4 | 30w | 110 | 11,246 |
| 5 | 39.8w | 121 | 12,005 |
| 6 | 54.3w | 131 | 14,052 |

Performance 92" Models

| Speed | Motor Wattage | RPM | Airflow (m3/hr) |
|-------|---------------|-----|-----------------|
| 1 | 12w | 75 | 3,610 |
| 2 | 15.7w | 86 | 7,796 |
| 3 | 22.5w | 93 | 11,152 |
| 4 | 30.4w | 105 | 12,896 |
| 5 | 40w | 116 | 14,058 |
| 6 | 54.8w | 127 | 16,235 |

Dimensions

This fan requires a minimum ceiling height of 2.7m.

Canopy cover diameter
150mm

Supplied with a 250mm rod which results in larger than average ceiling to blade drop.



Extension Rods

| | | | |
|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| Matte Black 900mm | White 900mm | Matte Black 1800mm | White 1800mm |
| Without Light K505M/209A | Without Light K505M/109A | Without Light K505M/218A | Without Light K505M/118A |
| With Light K5061/209A | With Light K5061/109A | With Light K5061/218A | With Light K5061/118A |