

Last modification

2021-07-20

**LUC.G13-BK83-826**  
**9329501054239**



The LUC G series is a recessed single directional LED luminaire.

The modern design is small and discreet but bright and can therefore optimally illuminate and set the scene for walkways, driveways, gardens, and terraces. The light of the internal LEDs is emitted indirectly through a single opening and provides glare-free orientation lighting. Can be recessed floor or wall-mounted.

With an operating voltage of 8~26 volt and a water-protected rating of IP65, it is a versatile and safe lighting solution for outdoor areas. Other fixtures in the LUC series can be combined to form a complete outdoor space solution.

A 12 or 24 volt AC transformer is recommended to power up this fixture.

## Overview

<b>Family name</b>	Luc
<b>Item Type</b>	Inground Light (G)
<b>Mounting</b>	Recess

## Color / Material

<b>Diffuser Colour</b>	Clear
<b>Diffuser Material</b>	Glass

## Size

<b>Fixture Diameter (cm)</b>	4.2
<b>Fixture Height (cm)</b>	8.5

## Specification

<b>Voltage Input</b>	240V
<b>Wattage (max)</b>	3
<b>Globe Type</b>	LED integrated COB
<b>Globe / Light Source qty</b>	1
<b>Globe / Light Source included</b>	Yes
<b>Lumens</b>	200
<b>Color Kelvin</b>	3000k
<b>Color Rendering</b>	>84
<b>Dimmable</b>	No
<b>IP rating</b>	IP65

All representations within this document are subject to copyright. ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.  
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

Warranty	3 Years
<a href="#">Barcode</a>	
GTIN	9329501054239
<a href="#">Pricing</a>	
PRICE - RRP incGST	53.8



Last modification

2021-07-20

**LUC.G23-BK83-826**  
**9329501056066**



The LUC G series is a recessed dual-directional LED luminaire.

The modern design is small and discreet but bright and can therefore optimally illuminate and set the scene for walkways, driveways, gardens, and terraces. The light of the internal LEDs is emitted indirectly through a dual opening and provides glare-free orientation lighting. Can be recessed floor or wall-mounted.

With an operating voltage of 8~26 volt and a water-protected rating of IP65, it is a versatile and safe lighting solution for outdoor areas. Other fixtures in the LUC series can be combined to form a complete outdoor space solution.

A 12 or 24 volt AC transformer is recommended to power up this fixture.

## Overview

<b>Family name</b>	Luc
<b>Item Type</b>	Inground Light (G)
<b>Mounting</b>	Recess

## Color / Material

<b>Diffuser Colour</b>	Clear
<b>Diffuser Material</b>	Glass

## Size

<b>Fixture Diameter (cm)</b>	4.2
<b>Fixture Height (cm)</b>	8.5

## Specification

<b>Voltage Input</b>	240V
<b>Wattage (max)</b>	3
<b>Globe Type</b>	LED integrated COB
<b>Globe / Light Source qty</b>	1
<b>Globe / Light Source included</b>	Yes
<b>Lumens</b>	400
<b>Color Kelvin</b>	3000k
<b>Color Rendering</b>	>84
<b>Dimmable</b>	No
<b>IP rating</b>	IP65

All representations within this document are subject to copyright. ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.  
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

Warranty 3 Years

[Barcode](#)  
GTIN 9329501056066

[Pricing](#)  
PRICE - RRP incGST 63.8

