

Last modification

2021-07-20

LUC.G23-BK83-826

9329501056066



The LUC G series is a recessed dual-directional LED luminaire.

The modern design is small and discreet but bright and can therefore optimally illuminate and set the scene for walkways, driveways, gardens, and terraces. The light of the internal LEDs is emitted indirectly through a dual opening and provides glare-free orientation lighting. Can be recessed floor or wall-mounted.

With an operating voltage of 8–26 volt and a water-protected rating of IP65, it is a versatile and safe lighting solution for outdoor areas. Other fixtures in the LUC series can be combined to form a complete outdoor space solution.

A 12 or 24 volt AC transformer is recommended to power up this fixture.

Overview

Family name	Luc
Item Type	Inground Light (G)
Mounting	Recess

Color / Material

Diffuser Colour	Clear
Diffuser Material	Glass

Size

Fixture Diameter (cm)	4.2
Fixture Height (cm)	8.5

Specification

Voltage Input	240V
Wattage (max)	3
Globe Type	LED integrated COB
Globe / Light Source qty	1
Globe / Light Source included	Yes
Lumens	400
Color Kelvin	3000k
Color Rendering	>84
Dimmable	No
IP rating	IP65

All representations within this document are subject to copyright. ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

Data Sheet

Telbix.

Warranty 3 Years

Barcode

GTIN 9329501056066

Pricing

PRICE - RRP incGST 63.8



All representations within this document are subject to copyright. ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.