

# PHARE (GU10) SERIES

## Exterior Surface Mounted Wall Pillar Lights & Bollard Lights

### Product Features:


- Input voltage: 110-265V AC
- Material: aluminium / acrylic / 316 stainless steel
- Lamp holder: GU10 (Max.35W halogen globe)
- Globe not included
- IP rating: IP65 for wall lamps; IP54 for bollard lights
- Bollard lights can not be used inground
- To maintain the IP rating please use circular cable in junction
- For parallel and single connection we recommend using an appropriate IP68 connector (CLA Connector: CONN001 & CONN002)



PHARE01G



PHARE02G



Exterior Lighting



PHARE03G



PHARE03EXT








PHARE04G



PHARE04EXT



PHARE05G



Part No.	Description	Colour	Lamp Holder	Weight (kg)	Box (cm)	Carton QTY
PHARE01G	WALL PILLAR UP/DN BLK Anti Glare GU10	Matte Black	2xGU10	0.81	8.5x9.5x28	1/20
PHARE02G	WALL PILLAR UP/DN ALU TITANIUM Anodized GU10	Titanium Anodized	2xGU10	0.81	8.5x9.5x28	1/20
PHARE03G	BOLLARD ALU BLK Anti Glare GU10	Matte Black	1xGU10	1.01	10x10x47	1/10
PHARE04G	BOLLARD ALU TITANIUM Anodized Anti Glare GU10	Titanium Anodized	1xGU10	1.01	10x10x47	1/10
PHARE05G	BOLLARD SS316 Anti Glare GU10	Stainless Steel	1xGU10	2.00	10x10x47	1/10
PHARE03EXT	BOLLARD EXTENSION MATT BLK Screw in H380mm for PHARE03M/G	Matte Black	-	0.45	40x7x7	1/25
PHARE04EXT	BOLLARD EXTENSION TITANIUM Screw in H380mm for PHARE04M/G	Titanium Anodized	-	0.45	40x7x7	1/25

\*These bollards are designed for mounting on a solid surface such as a concrete path or sturdy timber decking

\*To avoid disappointment and warranty problems, please ensure the IP Rating of the chosen product is relevant for the intended use.

\*Must be installed by a licenced electrician (Installation instructions sheet provided in each product box)