



## SERDA PE184-WH

15365P

### SKU

SERDA PE184-WH

### GTIN

9329501083437

### DESCRIPTION

The Serda pendant range combines contemporary design with advanced lighting performance. Each pendant features an integrated LED light source with adjustable 3CCT colour temperatures ranging from 2700K to 5000K, allowing seamless transition from warm to cool illumination. A built-in touch sensor provides smooth, intuitive dimming control at your fingertips.

Available in both circular and linear formats, the Serda collection offers versatility for modern spaces. The linear pendant includes a practical yoyo up/down suspension system, enabling effortless height adjustment to suit any installation or ambience.

Stylish, efficient, and user-friendly, Serda brings refined architectural lighting to residential and commercial environments.

### CATEGORIES

Pendants

### USAGE

Indoor Lighting

### VOLTAGE INPUT

240V

### FIXTURE COLOR

White

### TOTAL WATTAGE (MAX)

46

### FIXTURE MATERIAL

Aluminium, Iron, PVC

### FIXTURE LENGTH (CM)

184.00

### FIXTURE WIDTH (CM)

5.00

### FIXTURE HEIGHT (CM)

5.50

### FIXTURE WEIGHT (KG)

3.30

### CANOPY PROJECTION (CM)

6.00

### CANOPY WIDTH (CM)

6.50

### CANOPY LENGTH (CM)

48.00

### SUSPENSION LENGTH (CM)

180.00

### HEIGHT ADJUSTABLE?

Yes

### GLOBE TYPE

LED integrated SMD

### GLOBE / LIGHT SOURCE INCLUDED

Yes

### LUMENS

2310

### COLOR TEMPERATURE

Warm White; Natural White; Cool White

### COLOR KELVIN

3 CCT (2700k - 4000k - 5000k)

### DIMMABLE

Touch

### ELECTRICAL PROTECTION

CLASS I - HIGH VOLTAGE, EARTH REQUIRED

### IP RATING

IP20

### APPROVALS

RCM

### REPLACEMENT WARRANTY

\*3 Years

**CARE INSTRUCTIONS**

---

Do not use strong liquid cleaners, Wipe clean with a dry cloth, Aluminium, Brass and Stainless Steel will naturally oxidised and change overtime. Exterior products require regular four (4) monthly cleaning and maintenance to ensure they do not accumulate dirt or other environmental deposits. Wipe the product with a mild detergent and warm water to remove surface deposits. Rinse with fresh water and wipe dry with a soft cloth. An extra temporary protection barrier of water displacement oil can help to maintain the surface, such as WD40, sprayed onto a soft cloth and rubbed onto the surface.

**BOX WEIGHT (KG)**

---

5.40

**BOX LENGTH (CM)**

---

186.00

**BOX WIDTH (CM)**

---

17.00

**BOX HEIGHT (CM)**

---

8.50

**MASTER CARTON LENGTH (CM)**

---

0.00

**MASTER CARTON WIDTH (CM)**

---

0.00

**MASTER CARTON HEIGHT (CM)**

---

0.00

**MASTER CARTON WEIGHT (KG)**

---

0.00

**IMAGE - DIMENSIONS**

---

