



SERDA PE63-WH

15366P

SKU

SERDA PE63-WH

GTIN

9329501083413

DESCRIPTION

The Serda pendant range combines contemporary design with advanced lighting performance. Each pendant features an integrated LED light source with adjustable 3CCT colour temperatures ranging from 2700K to 5000K, allowing seamless transition from warm to cool illumination. A built-in touch sensor provides smooth, intuitive dimming control at your fingertips.

Available in both circular and linear formats, the Serda collection offers versatility for modern spaces. The linear pendant includes a practical yoyo up/down suspension system, enabling effortless height adjustment to suit any installation or ambience.

Stylish, efficient, and user-friendly, Serda brings refined architectural lighting to residential and commercial environments.

CATEGORIES

Pendants

USAGE

Indoor Lighting

VOLTAGE INPUT

240V

FIXTURE COLOR

White

TOTAL WATTAGE (MAX)

36

FIXTURE MATERIAL

Aluminium, Iron, PVC

FIXTURE HEIGHT (CM)

5.50

FIXTURE DIAMETER (CM)

69.00

FIXTURE WEIGHT (KG)

3.00

CANOPY DIAMETER (CM)

20.00

CANOPY PROJECTION (CM)

4.00

SUSPENSION LENGTH (CM)

200.00

HEIGHT ADJUSTABLE?

Yes

GLOBE TYPE

LED integrated SMD

GLOBE / LIGHT SOURCE INCLUDED

Yes

LUMENS

1860

COLOR TEMPERATURE

Warm White; Natural White; Cool White

COLOR KELVIN

3 CCT (2700k - 4000k - 5000k)

DIMMABLE

Touch

ELECTRICAL PROTECTION

CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP RATING

IP20

APPROVALS

RCM

REPLACEMENT WARRANTY

*3 Years

CARE INSTRUCTIONS

Do not use strong liquid cleaners, Wipe clean with a dry cloth, Aluminium, Brass and Stainless Steel will naturally oxidised and change overtime. Exterior products require regular four (4) monthly cleaning and maintenance to ensure they do not accumulate dirt or other environmental deposits. Wipe the product with a mild detergent and warm water to remove surface deposits. Rinse with fresh water and wipe dry with a soft cloth. An extra temporary protection barrier of water displacement oil can help to maintain the surface, such as WD40, sprayed onto a soft cloth and rubbed onto the surface.

BOX WEIGHT (KG)

5.60

BOX LENGTH (CM)

68.00

BOX WIDTH (CM)

68.00

BOX HEIGHT (CM)

9.00

MASTER CARTON LENGTH (CM)

0.00

MASTER CARTON WIDTH (CM)

0.00

MASTER CARTON HEIGHT (CM)

0.00

MASTER CARTON WEIGHT (KG)

0.00

IMAGE -DIMENSIONS

